Technical data sheet

Device installation trunking, desk trunking







GEK-S device installation trunking suitable for installation on desks, etc. The visible surfaces of the painted GEK-S device installation trunking are laminated. The trunking system possesses self-contacting locking straps to accept a sheet steel partition. The equipotential bonding between the trunking bases takes place using the coupling. The protective measure and the equipotential bonding is guaranteed between the cover and the base by the self-contacting trunking cover. The actual system opening is 76.5 mm. The cover must be ordered separately.



St

Steel

Master data

| Item number | 6282700 |
|--|------------------------------|
| Туре | GEK-SA133110RW |
| Description 1 | Device installation trunking |
| Description 2 | asymmetrical |
| Manufacturer | OBO |
| Dimension | 133x110x2000 |
| Colour | Pure white; RAL 9010 |
| Material | Steel |
| Smallest sales unit | 2 |
| Unit of quantity | Metre |
| Weight | 332 kg |
| Weight unit | kg/100 m |
| CO2 Footprint (GWP) Cradle-to- Gate | 7,6511 kg CO2e / 1 Meter |

Technical data sheet

Device installation trunking, desk trunking





Dimensions 133

| | 2,000 mm |
|--------|----------|
| Width | 110 mm |
| Height | 133 mm |

Technical data

| Number of covers | 1 |
|-----------------------------------|-----------------------|
| Number of insertable partitions | 1 |
| Rear panel version (inner side) | With locking lugs |
| Rectangular shape | no |
| Base perforation | with base perforation |
| Halogen-free | yes |
| Cable retaining clip | no |
| Duct connector | no |
| Cover mounting type | Internal |
| Mounting perforation in base | yes |
| Usable cross-section | 9950 mm² |
| Cover supplied | no |
| Cover width | 76.5 mm |
| Protection rating | IP30 |
| Protective film | yes |
| Protection rating IK code | IK10 |
| Symmetrical | no |
| Permitted temperature range, max. | 60 °C |
| Permitted temperature range, min. | -25 °C |