

# Technical data sheet

## Internal corner, for cable trunking type LKM 60200

Item number: 6248160



Internal corner for changing the direction of the LKM trunking.  
Equipotential bonding without additional aids, between base and cover



|    |                  |
|----|------------------|
| St | Steel            |
| FS | Strip galvanized |

### Master data

|                                    |                          |
|------------------------------------|--------------------------|
| Item number                        | 6248160                  |
| Type                               | LKM I60200FS             |
| Description 1                      | Internal corner          |
| Manufacturer                       | OBO                      |
| Dimension                          | 60x200mm                 |
| Colour                             | zinc                     |
| Material                           | Steel                    |
| Surface                            | Strip galvanized         |
| Surface standard                   | DIN EN 10346             |
| Smallest sales unit                | 1                        |
| Unit of quantity                   | Piece                    |
| Weight                             | 57.5 kg                  |
| Weight unit                        | kg/100 pc.               |
| CO2 Footprint (GWP) Cradle-to-Gate | 2,3874 kg CO2e / 1 Piece |

# Technical data sheet


Internal corner, for cable trunking type LKM 60200

Item number: 6248160



## Dimensions

|             |        |
|-------------|--------|
| Length      | 160 mm |
| Width       | 200 mm |
| Height      | 64 mm  |
| Dimension a | 160 mm |



## Technical data

|                                   |                  |
|-----------------------------------|------------------|
| Version for                       | Base             |
| Fastening type                    | Base perforation |
| Maintain electrical functions     | no               |
| Halogen-free                      | yes              |
| Protection rating                 | IP30             |
| Protective film                   | no               |
| Protection rating IK code         | IK10             |
| Permitted temperature range, max. | 90 °C            |
| Permitted temperature range, min. | -5 °C            |
| Angle range, max.                 | 90 mm            |
| Angle range, min.                 | 90 mm            |