Technical data sheet

Underfloor duct, 2 pieces, 2-compartment, duct height 38 mm Item number: 7400267



Underfloor duct (2 piece) for routing cables in screed-covered underfloor systems, according to EN 50085-2-2. Removable and continuously lockable duct cover. With separating retainer in the duct base.

The profiled side walls offer a locking mechanism to lock the duct cover onto the duct base. The stiffening beads in the duct cover serve to create stability.





Master data

| Item number7400267TypeS2 25038-2Description 1Underfloor duct, 2-partDescription 22 compartmentsManufacturerOBODimension2000x250x38MaterialSteelSurfaceStrip galvanizedSurface standardDIN EN 10346 |
|--|
| Description 1Underfloor duct, 2-partDescription 22 compartmentsManufacturerOBODimension2000x250x38MaterialSteelSurfaceStrip galvanized |
| Description 22 compartmentsManufacturerOBODimension2000x250x38MaterialSteelSurfaceStrip galvanized |
| ManufacturerOBODimension2000x250x38MaterialSteelSurfaceStrip galvanized |
| Dimension2000x250x38MaterialSteelSurfaceStrip galvanized |
| Material Steel Surface Strip galvanized |
| Surface Strip galvanized |
| |
| Surface standard DIN EN 10346 |
| |
| Smallest sales unit 2 |
| Unit of quantity Metre |
| Weight 387.994 kg |
| Weight unit kg/100 m |

Dimensions

| Length | 2,000 mm |
|-------------|----------|
| Width | 250 mm |
| Height | 38 mm |
| Dimension a | 110 mm |
| Dimension b | 140 mm |
| Dimension h | 38 mm |

Technical data sheet

Underfloor duct, 2 pieces, 2-compartment, duct height 38 mm Item number: 7400267



Technical data

| Number of fixed partitions | 1 |
|----------------------------|----------------|
| Number of compartments | 2 St. |
| Floor plate | yes |
| Application area | Screed-covered |
| Decouplable | no |
| Trunking width, min. | 250 mm |
| Duct height, min. | 38 mm |
| Usable cross-section | 8524 mm² |
| Removable cover | yes |
| Cross-section, draw a | 3717 mm² |
| Cross-section, draw b | 4807 mm² |
| | |