

Technical data sheet

Underfloor duct, 2 pieces, 3-compartment, duct height 28 mm

Item number: 7400287



Underfloor duct (2 piece) for routing cables in screed-covered underfloor systems, according to EN 50085-2-2. Removable and continuously lockable duct cover. With separating retainer in the duct base. The profiled side walls offer a locking mechanism to lock the duct cover onto the duct base. The stiffening beads in the duct cover serve to create stability.



St Steel

FS Strip galvanized

Master data

| | |
|---------------------|-------------------------|
| Item number | 7400287 |
| Type | S3 35028-2 |
| Description 1 | Underfloor duct, 2-part |
| Description 2 | 3 compartments |
| Manufacturer | OBO |
| Dimension | 2000x350x28 |
| Material | Steel |
| Surface | Strip galvanized |
| Surface standard | DIN EN 10346 |
| Smallest sales unit | 2 |
| Unit of quantity | Metre |
| Weight | 503.717 kg |
| Weight unit | kg/100 m |

Dimensions

| | |
|-------------|----------|
| Length | 2,000 mm |
| Width | 350 mm |
| Height | 28 mm |
| Dimension a | 120 mm |
| Dimension b | 110 mm |
| Dimension h | 28 mm |

Technical data sheet

Underfloor duct, 2 pieces, 3-compartment, duct height
28 mm

Item number: 7400287



Technical data

| | |
|----------------------------|----------------------|
| Number of fixed partitions | 2 |
| Number of compartments | 3 St. |
| Floor plate | yes |
| Application area | Screed-covered |
| Decouplable | no |
| Trunking width, min. | 350 mm |
| Duct height, min. | 28 mm |
| Usable cross-section | 8722 mm ² |
| Removable cover | yes |
| Cross-section, draw a | 2944 mm ² |
| Cross-section, draw b | 2834 mm ² |