## **Technical data sheet**

## Junction box T 100, plug-in seal, terminal strip





Junction box with terminal strip for the connection of cables and lines indoors and in protected outdoor areas. Rectangular design with plug-in seals to the sides and knock-out entries in the bottom. Suitable for wall and ceiling mounting and on mounting panels. With the option to fasten inside and to mount via the corner domes. Cover with quick lock, sealable. Made from halogen-free and UVresistant materials.

Junction box according to DIN EN 60670. Flame-resistant to DIN EN 60695/2/11, test temperature 650  $^{\circ}$ C. Impact resistance IK07 according to DIN EN 50102.























Polypropylene

R/A		ter	٨.	-+-
IVI	as	Lei	u	ala

Item number	2007436	
Type	T 100 KL	
Description 1	Junction box	
Description 2	with terminal strip + entries	
Manufacturer	OBO	
Dimension	150x116x67	
Colour	Light grey; RAL 7035	
Material	Polypropylene	
Smallest sales unit	1	
Unit of quantity	Piece	
Weight	29.5 kg	
Weight unit	kg/100 pc.	
CO2 Footprint (GWP) Cradle-to- Gate	1,2789 kg CO2e / 1 Piece	

## **Technical data sheet**

# Junction box T 100, plug-in seal, terminal strip



**Item number: 2007436** 

# Dimensions 34 34 51 7100 PBB & 91 PBB

Length	150 mm
Width	116 mm
Height	67 mm

### **Technical data**

Expandable	yes		
No. of entries	10		
Number of terminals	5		
Type of entry	Plug-in seal		
Type of entry	Cable		
Type of housing penetration	Cuttable stepped membrane		
Measured insulation voltage Vi	500 V		
Equipment	Teminal		
Cover	Not transparent		
Cover fastening	Screwed		
Entry from rear	yes		
Entries	10 x M25		
Explosion-tested version	no		
Flame-resistant	acc. to VDE 0471/DIN 695 Part 2-1, test temperature 650°C		
Shape	Rectangular		
Maintain electrical functions	Without		
For Ex zone	Without		
For Ex zone gas	Without		
For Ex zone dust	Without		
Fibre-glass reinforced	no		
Halogen-free	yes		
Clear internal dimensions	136x102x57 mm		
With screening	no		
with lid	yes		
Mounting type	Wall/ceiling mounting		
Nominal cross-section, min.	10 mm²		
Nominal voltage	500 V		
Sealable	yes		
Protection rating	IP66		
Protection rating IK code	IK07.		

# **Technical data sheet**

# Junction box T 100, plug-in seal, terminal strip



**Item number: 2007436** 

Technical data		
	Permitted temperature range, max.	60 °C
	Permitted temperature range, min.	-5 °C
	Transparent lid	no
	Weatherproof	no