## **Technical data sheet**

# UDHOME-ONE floor socket, without floor covering recess, single VDE socket, stainless steel Item number: 7368288





Square floor socket for use in dry-care systems and screed floors in indoor areas. Installation housing with pre-marked insertion openings for pipes (M20/M25). Cover adjustable to top edge of floor covering using four height-adjustment supports. The minimum installation depth is 75 mm, the height-adjustment range +30 mm. Frame and cover made of stainless steel and visible in the floor covering. Cover with decorative plate. A protective contact socket (VDE) is included in the delivery. A data socket can optionally be installed in the data technology plate. When delivered, the item is closed with a blanking plate.





Stainless steel

#### Master data


| 7368288                        |
|--------------------------------|
| UDHOME-ONE GV V                |
| Floor socket                   |
| with protective contact socket |
| OBO                            |
| 140x140x75                     |
| Stainless steel                |
| 1                              |
| Piece                          |
| 220 kg                         |
| kg/100 pc.                     |
| 12,0365 kg CO2e / 1 Piece      |
|                                |

## **Technical data sheet**


UDHOME-ONE floor socket, without floor covering recess, single VDE socket, stainless steel Item number: 7368288



### Dimensions



| Length | 140 mm |
|--------|--------|
| Width  | 140 mm |
| Height | 75 mm  |



### Technical data

| Number of installable devices                     | 2                       |
|---|-------------------------|
| Number of SCHUKO sockets                          | 1                       |
| Version for                                       | Square                  |
| Cable outlet version                              | Swivellable cord outlet |
| Equipment   | Single VDE socket       |
| Floor covering protection frame                   | no                      |
| Floor care  | Dry                     |
| Cover version                                     | Decorative plate        |
| Seal installation option                          | no                      |
| Application when used                             | 6.101.1 Dry floor care  |
| Application when unused                           | 6.101.1 Dry floor care  |
| Floor height, max.                                | 105 mm                  |
| Floor height, min.                                | 75 mm                   |
| Suitable for raised floor installation            | yes                     |
| Suitable for screed-flush closed underfloor ducts | no                      |
| Suitable for screed-covered underfloor ducts      | no                      |
| Suitable for cavity floor installation            | yes                     |
| Suitable for wet care                             | no                      |
| Suitable for underfloor ducts                     | no                      |
| Device support to accept mounting boxes           | no                      |
| With floor covering recess                        | no                      |
| Height-adjustment range, max.                     | 105 mm                  |
| Height-adjustment range, min.                     | 75 mm                   |
| Protection rating (IP) when used                  | IP20                    |
|   |                         |

## **Technical data sheet**

UDHOME-ONE floor socket, without floor covering recess, single VDE socket, stainless steel Item number: 7368288



| Technical data |                                    |             |
|----------------|------------------------------------|-------------|
|                | Protection rating (IP) when unused | IP40        |
|                | Protection rating IK code          | IK10        |
|                | Heavy-duty version                 | no          |
|                | Vertical load, large area          | to 15,000 N |
|                | Vertical load, small area          | to 3,000 N  |
|                | Approvals                          | VDE         |
|                | Opening mechanism                  | Handle      |