Technical data sheet

UDHOME2 floor socket, without floor covering recess, freely equippable, stainless steel, decorative plate: angelhair ltem number: 7368261





Square floor socket for use in dry-care cavity and screed floors in indoor areas. Installation housing with pre-marked insertion openings for pipes (M20/M25). Cover adjustable to top edge of floor covering using four height-adjustment supports. The minimum installation depth is 100 mm, the height-adjustment range 35 mm.Frame and cover made of stainless steel and visible in the floor covering. Cover with Angelhair decorative plate. Empty housing for up to 2 Modul 45® devices in the mounting support and 2 data sockets in the optional data technology support.



Master data

Item number	7368261	
Туре	UDHOME2 GV D1	
Description 1	Floor socket	
Description 2	unequipped, Angelhair	
Manufacturer	OBO	
Dimension	140x140x110	
Smallest sales unit	1	
Unit of quantity	Piece	
Weight	220 kg	
Weight unit	kg/100 pc.	
CO2 Footprint (GWP) Cradle-to- Gate	12,5387 kg CO2e / 1 Piece	

Technical data sheet

UDHOME2 floor socket, without floor covering recess, freely equippable, stainless steel, decorative plate: angelhair Item number: 7368261



Dimensions Length Width 140 mm Height 100 mm

	ica	

Number of installable devices	2	
Version for	Square	
Cable outlet version	Swivellable cord outlet	
Equipment	Empty housing	
Floor covering protection frame	no	
Floor care	Dry	
Seal installation option	no	
Application when used	6.101.1 Dry floor care	
Application when unused	6.101.1 Dry floor care	
Floor height, max.	135 mm	
Floor height, min.	100 mm	
Suitable for raised floor installation	yes	
Suitable for screed-flush closed underfloor ducts	no	
Suitable for screed-covered underfloor ducts	no	
Suitable for cavity floor installation	yes	
Suitable for wet care	no	
Suitable for underfloor ducts	no	
Device support to accept mounting boxes	no	
With floor covering recess	no	
Nominal size for device installation units	2	
Standard	EN 50085-2-2	
Frame version	Floor covering contact edge	
Protection rating (IP) when used	IP20	
Protection rating (IP) when unused	IP40	
Protection rating IK code	IK10	
Heavy-duty version	no	
Vertical load, large area	to 15,000 N	

Technical data sheet

UDHOME2 floor socket, without floor covering recess, freely equippable, stainless steel, decorative plate: angelhair Item number: 7368261



Technical data		
	Vertical load, small area	to 3,000 N
	Approvals	VDE
	Opening mechanism	Handle